



L U X - S F I 3 0 M

CARACTÉRISTIQUES GÉNÉRALES

DESCRIPTION	Hotte de cuisine
INSTALLATION	Îlot

CONCEPTION


MATÉRIEL	Acier inoxydable 430 / Verre trempé
VOLTS	120 VAC
HERTZ	60
AMPÈRES	5
ASPIRATION 1 ^{ÈRE} VITESSE	200 PCM
ASPIRATION 6 ^E VITESSE	870 PCM
DÉCIBELS (1 ^{ÈRE} VITESSE)	25 DBA
DÉCIBELS (6 ^E VITESSE)	63 DBA
COMMANDE	Mécanique, 3 vitesses
FILTRES	Aluminium / 1 mc / 15-3/4 x 11"
DIAMÈTRE DE LA SORTIE	6" rond
LUMIÈRE	4 x GU10 Halogène 20 W
AVEC PLAQUE AU GAZ	Autorisé
CONFORMITÉS	UL 507 et CSA C22.2 N° 113-10
GARANTIE	1 an







L U X - S F I 3 0 M

PERFORMANCE D'ASPIRATION



DESSIN TECHNIQUE (POUCES)





L U X - S F I 3 0 M

GENERAL CHARACTERISTICS

DESCRIPTION	Range hood
INSTALLATION	Island mounted

DESIGN FEATURES


MATERIAL	430 stainless steel / Tempered glass
VOLTS	120 VAC
HERTZ	60
AMPS	5
SUCTION (1 st SPEED)	200 CFM
SUCTION (6 th SPEED)	870 CFM
DECIBELS (1 st SPEED)	25 DBA
DECIBELS (6 th SPEED)	63 DBA
SWITCH	Mechanical, 3 speeds
FILTERS	Aluminum / 1 pc / 15-3/4" x 11"
DUCTING SIZE	6" round
LIGHTS	4 x GU10 Halogen 20 W
USE WITH GAS COOKTOP	Allowed by regulation
COMPLIANCES	UL 507 et CSA C22.2 N° 113-10
WARRANTY	1 year






L U X - S F I 3 0 M

AIR FLOW PERFORMANCE



TECHNICAL DRAWING (INCHES)



Recommended installation and maintenance : please consult our installalation guide.

LUXCANADA.CA